

# AquaRite® LT SV

**EXPERT LINE**



YEARS OF WARRANTY  
**3** STANDARD **4<sup>TH</sup>** 8000 HOURS



As defined by EN 17645.  
 Go to report pages to see  
 the complete detail by item.

## AN AFFORDABLE, HIGH QUALITY SALT CHLORINATOR WITH TRANSPARENT CELL

- **Automatic pH correction kit** available as an optional extra
- **Simple** to install, simple to use
- **Closed pool cover detection** for an instant reduction in chlorine production
- **Transparent cell** to enable a visual check of the production. Gas sensor included
- **Options available** for this easy-to-use salt chlorinator
- **Optional ORP kit** regulates the chlorine production



### INCLUDED



### AQUARITE® LT SV

### TRANSPARENT CELL

### AVAILABLE OPTIONS

Description	AQR-LTO-SV16	AQR-LTO-SV22	AQR-LTO-SV33	AQR-LTO-SV50
Maximum production Cl <sub>2</sub> /h	16 g/h	22 g/h	33 g/h	50 g/h
Salt concentration	From 3gr up to 100 gr Na/Cl			
Average pool volume	75 m³	100 m³	150 m³	250 m³
Display	2,8" TFT Color			
Power supply	230Vac 50/60Hz			
Dimensions	270 x 220 x 115 mm			
Electronic box	Fireproof black ABS plastic			
Front cover	Black ABS plastic			
Output	8-15A	8-20A	10-15A	10-16A
Consumption	120W	160W	150W	170W
Temperature control	Yes			
Automatic cleaning	Operates by reverse polarity			
Pool cover	Programmable 0 – 100% production as a function of pool cover being open or closed			
Electrolysis cell	4 Titanium cell plates MONOPOLAR	5 Titanium cell plates MONOPOLAR	7 Titanium cell plates MONOPOLAR	10 titanium plates MONOPOLAR
Minimum flow	5 m³/h	7 m³/h	9 m³/h	9 m³/h
Dimension cell plates	200 x 45 mm	200 x 45 mm	200 x 45 mm	400 x 45 mm
Material cell housing	Plastic PVC transparent			
Cell fastener	Thread for an easy installation			
Diameter tube connection	63 mm			
Dimension cell	355 x 305 x 305 mm			520 x 305 x 305 mm
Cell cable size	(3 x 4) x 1.5 m			(2 x 4) x 1,5m
Gas sensor	Included in the cell			
Flow Switch	Included			Not included
Maximum pressure	4 kg/cm²			
Maximum temperature	45 °C			
PH standard probe kit	BKPER-OPTION-PH (1.5 L/h peristaltic pump)			
ORP standard probe kit	E-OPTION-REDOX			
Pool Terre	KV02			



ORP kit Standard probe (optional)



pH correction kit (optional)